



Division09

Section **09 94 20**

Textured Wall Finish

Tobias Green Interior Wall Finish - Pure

Project Name: _____
 Submittal No.: _____
 Contractor: _____
 Architect: _____

Test Data:

Property & Test Method	Results
Volatile Content (VOC) per EPA Reference Test Method 24 (40CFR Part 60, Appendix A)	VOC (grams/liter) = 1 g/l.
Fungus Resistance , ASTM G 21:	Rating = Zero, no mold or fungus growth.
Fade Resistance , ASTM D 2565:	Pass rating = 2. No significant change inspected from 1-2 feet after 200 hour exposure.

Product Description:

Decorative wall coating for horizontal and vertical surfaces.

Single-component, pre-mixed water based wall finish coating with factory-mixed colorants, capable of installation in varying surface textures over a wide range of prepared substrates.

Complies with Green Seal GS-11 VOC requirements for flat interior coatings, and meets the LEED-NC 2.1 VOC requirement for Low-Emitting Paints and Coatings.

Certifications

Organization	Label
GreenSeal	GS-11

Where To Use:

Tobias Pure® Wall Finish may be used on a variety of prepared building substrates, where an environmentally safe, trowelled or machine applied textured finish with integral color is desired.

Mold-resistant, color-fast, extremely low-VOC, Tobias Pure® Wall Finish produces a broad spectrum of rich and multi-pigmented shades in a single application and can be applied with many different techniques to achieve a wide variety of textures.

Gypsum based single-component mixture requires minimal preparation and clean-up.

Yield

A five gallon bucket will cover approximately 350 square feet in a smooth troweled texture. Yields will be reduced for heavier textures.

Limitations:

Shelf Life is 6 months with proper storage.

Interior Use Only.

Working time, 60-120 minutes.

Recommended For Professional Use.

Textures

Many different textures and combinations are possible. Refer to the Application Guide.

Colors

Twenty-four (24) standard colors are available and custom mixes are possible.

Product Data: Tobias Pure Wall Finish

How to Apply:

Substrate Preparation

Examine surfaces to identify conditions that might interfere with proper bonding of coating. Test for presence of oil or grease by wetting surface and examining for beading water droplets. Look for signs of algae, mold, or mildew. Look for dirt, paint, mortar droppings, patching compounds, loose tile, cracked substrates, and similar conditions.

Preparation and Priming

Clean surfaces of all material that might interfere with proper bonding of coating. Wash with approved cleaning solution at cleaning solution manufacturer's recommended dilution, to remove algae, mold, and mildew. Wash oil and grease spots with trisodium phosphate and water; soak if necessary.

Apply flat primer to gypsum board, particle board, cement board, concrete or cinder block. Tinting the primer to match selected color will reduce holidays.

Mixing & Application

Mixing: Product is ready to apply straight from the bucket. Mix with electric paddle if the mixture is visibly separated, (which can occur during shipping) or if more than three (3) weeks have passed from the date stamped on the bucket to produce best quality and consistent color throughout.

Do not add water, other liquids, colorants or substances to the mixture. Do not scoop mixture out of the bucket with metal tools; ensure edges of paddles are smooth. Avoid scraping plastic from the sides of the bucket into the mixture. Bits of plastic in the mix will cause surface streaking in the finished work.

Trowel or machine application only. Do not use roller or spray application. Do not wet the trowel. Brush application is acceptable only for moldings and certain specific special textures. Tools: Various surface textures required specific tools as recommended by Tobias GREEN. Refer to the Application Guide for more information.

Begin application at the corner of the wall and proceed. Complete one wall or plane at a time. Avoid stopping in the middle of the wall or plane to prevent cold lines. Apply Interior Wall Finish no more than 1/16" thick. More than 1/8" material thickness in an application will create a crackling effect.

Clean Up

Remove spatters, spills, overspray from adjacent surfaces not to be finished using methods recommended by wall finish manufacturer. Take care not to damage these surfaces, perform all cleaning with methods approved by finish manufacturer.

Curing

Allow each coat to dry thoroughly. Always use the recommended number of coats for each texture. Tobias Green Interior Wall Finishes requires a minimum of two coats to achieve the optimum look and durability.

Precautions

Remove electrical plates, hardware, light fixture trim, escutcheons, and fittings prior to preparing surfaces or finishing. Tape around windows, doors, moldings, baseboards etc. Remove tape between coats when Interior Wall Finish is damp, and re-tape when the first coat is dry. Correct defects and clean surfaces which affect work. Remove or repair existing coatings that exhibit surface defects. Remove all wall paper or wall coverings, including all glue and adhesives. Feather-edge patches to make finished edges inconspicuous.

Health and Safety

Follow good safety and industrial hygiene practices during handling and installing of all products and systems. Always wear masks or respirators and eye protection while sanding. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read the MSDS and related literature before specification and/or installation.

For full Product Safety information call us at 866-369-4721.

TOBIAS GREEN INTERIOR WALL FINISHES, INC. MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS: This document is intended as a product submittal only. For complete product information regarding TOBIAS GREEN products please refer to the TOBIAS GREEN Installation and Application instructions and MSDS. **Notice** We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than intended use. Our liability is expressly limited to replacement of defective material. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from the date of it was reasonably should have been discovered. **Trademark** All rights reserved. TOBIAS GREEN, the TOBIAS GREEN logo are registered trademarks of TOBIAS GREEN in the United States and other countries. Information is subject to change without notice.

Tobias Green Interior Wall Finishes, Inc.®, P.O. 190, Forestville, CA 95436 • www.TobiasGreenWallFinishes.com
Toll Free 866-369-4721, sales@TobiasGreenWallFinishes.com